ATM Instruments ATM Instruments ATM Instruments ATM Instruments ATM Instruments ATM Instruments ATM Instruments ATM Instruments

INSTRUMENTS

Français

MADE en ITALIE

Raccords en Laiton Nickelé pour Circuit Air Comprimé - Eau - Hydraulique

Utilisation dans des circuits de Air Comprimé , Eau Hydraulique et fluides non corrosif au laiton.

Caractéristique Technique :
Pression Mini : -1 bar (-0,100 Mpa) Vide.
Pression Maxi : 150 bar (15 Mpa).
Température mini / maxi : -20 + 90°C.
Raccordements : Gaz conique ISO 7.1-BS21-DIN 2999.
Gaz cylindrique ISO 228 classe A.

Filetage conique	1/8"	1/4"	3/8"	1/2"	3/4"	1"
PN	150 bar	100 bar	75 bar	85 bar	80 bar	50 bar
Filetage cylindrique	1/8"	1/4"	3/8"	1/2"	3/4"	1"
PN	150 bar	100 bar	75 bar	85 bar	80 bar	50 bar

ATM Instruments - 158, rue de l'Artisanat - Parc du Calvi 74330 EPAGNY-France
Tél. 0033-04.50.46.08.73 - Fax. 0033-04.80.80.61.79
E-mail : contact@atm-instruments.com - Site: www.atm-instruments.com

ATM Instruments ATM Instruments ATM Instruments ATM Instruments ATM Instruments ATM Instruments ATM Instruments ATM Instruments ATM Instruments

INSTRUMENTS

Français

MADE en ITALIE

Raccords en Laiton Nickelé pour Circuit Air Comprimé - Eau - Hydraulique

Raccord L
M/F Conique
Raccord : 1/8" - 1/4"
3/8" - 1/2" - 3/4" - 1 "

Raccord L
F/F Conique
Raccord : 1/8" - 1/4"
3/8" - 1/2" - 3/4" - 1 "

Raccord L
M/M Conique
Raccord : 1/8" - 1/4"
3/8" - 1/2" - 3/4" - 1 "

Raccord Y
F/M/F
Raccord : 1/8" - 1/4"
3/8" - 1/2"

Raccord Y
F/F/F
Raccord : 1/8" - 1/4"
3/8" - 1/2"

Raccord à Croix
F/F/F/F
Raccord : 1/8" - 1/4"
3/8" - 1/2"

Réduction Lisse
M/F
Raccord :
du 1/8" au 1"½

Raccord T
F/F/F
Raccord : 1/8" - 1/4"
3/8" - 1/2"

Raccord T
F/M/F
Raccord : 1/8" - 1/4"
3/8" - 1/2"

Raccord T
M/M/M
Raccord : 1/8" - 1/4"
3/8" - 1/2"

Raccord T
M/F/M
Raccord : 1/8" - 1/4"
3/8" - 1/2"

Raccord T
F/F/M
Raccord : 1/8" - 1/4"
3/8" - 1/2"

Raccord Cannelé
en Mâle
Raccord : 1/8" - 1/4"
3/8" - 1/2"
Du Ø6 eu Ø16 mm

Raccord Cannelé
en Femelle
Raccord : 1/8" - 1/4"
3/8" - 1/2"
Du Ø6 eu Ø12 mm

Mamelon
M/M Conique
Raccord : 1/8" - 1/4"
3/8" - 1/2" - 3/4" - 1 "

Mamelon
M/M Cylindrique
Raccord : 1/8" - 1/4"
3/8" - 1/2" - 3/4" - 1 "

Réduction
F/M
Raccord : 1/8" - 1/4"
3/8" - 1/2" - 3/4" - 1 "

Manchon
F/F Cylindrique
Raccord : 1/8" - 1/4"
3/8" - 1/2" - 3/4" - 1 "

Réduction
M/F
Raccord : 1/8" - 1/4"
3/8" - 1/2" - 3/4" - 1 "

Bouchon mâle
Hexagonal
Raccord : 1/8" - 1/4"
3/8" - 1/2" - 3/4" - 1 "

Bouchon mâle
invisible
Raccord : 1/8" - 1/4"
3/8" - 1/2" - 3/4" - 1 "

Bouchon femelle
Hexagonal
Raccord : 1/8" - 1/4"
3/8" - 1/2" - 3/4"